ONE YEAR LIMITED WARRANTY

Winland Electronics, Inc. ("Winland") warrants to the end user/purchaser that each product of its manufacture shall be free from defects in material and factory workmanship for a period of one year from the date of purchase, when properly installed and operated under normal conditions according to Winland's instruction.

Winland's obligation under this warranty is limited to correcting, without charge, at its factory any part or parts thereof which shall be returned to the factory, by the original purchaser, transportation charges prepaid, within one year of the date of purchase and which upon examination, shall disclose to Winland's satisfaction to have been originally defective. Correction of such defects by repair to, or supplying replacements for, defective parts shall constitute fulfillment of all Winland's obligations to purchaser under this limited warranty. Repair service performed by Winland after one year from date of purchase will be for a reasonable service charge.

This limited warranty shall not apply to any of Winland's products which have been subject to misuse, negligence or accident or which have been repaired or altered outside of Winland's factory. The warranty is void if the Product's housing or cover is removed.

Winland shall not be liable for loss, damage or expense resulting, directly or indirectly, from the use of its products or any other cause.

This warranty shall be null and void in its entirety if: (i) the product is altered or modified in any way that is not consistent with the manufacturer's instructions, or (ii) the product is used with or connected to a device: (a) that such product is not intended to be used with or connected to, (b) is not otherwise consistent with the manufacturer's instructions, or (c) is not otherwise approved by the manufacturer.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSES, NON-INFRINGEMENT AND TITLE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, USAGE OF TRADE OR OTHERWISE. ALL OTHER REPRESENTATIONS MADE TO THE FUD USER/PURCHASER BY ANY OTHER PARTY ARE ALSO EXCLUDED. WINLAND SHALL NOT BE LIABLE TO ANY PERSON FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY DESCRIPTION, WHETHER ARISING OUT OF WARRANTY OR OTHER CONTRACT, NEGLIGENCE OR OTHER TORT, OR OTHERWISE. Under no circumstances shall Winland's liability under this limited warranty exceed the purchase price paid by the end user/purchaser for the product.

No person, agent or dealer is authorized to give warranties on behalf of Winland nor to assume for Winland any other liability in connection with any of its products.




WINLAND REMOTE BUZZER

Remote Annunciation for Winland products

CONTENTS

This package contains:

- 1 BZ-1 Remote Annunciator
- UAL Connectors
- 1 Installation/Operating Instructions Guide



BZ-1

SPECIFICATIONS

Power Requirement 11 to 26 VDC @ 10mA

Operating Temp 32° to 122°F (0° to 50°C); non-condensing environments

Indoor use only.

Buzzer 86 dB @ 30 cm @ 12 VDC. 3.5 kHz, continuous

Weight 0.65 lb (0.3 kg)

Dimensions 4.5 x 2.75 x 0.23" (11.43 x 6.99 x 0.58 cm)

Mounting Standard 1-gang switch mounting box

Warranty 1 Year Limited

Tech Support 8:00am - 5:00pm Central Time (800) 635-4269 • +1-507-625-7231 P www.winland.com



© 2012 Winland Electronics, Inc. Z1885 Rev E (08/2012) The BZ-1 Buzzer is intended for use with the Winland VehicleAlert and other Winland products. Up to 5 buzzers may be connected in parallel to provide remote annunciation throughout a home or business.

The BZ-1 is provided with a UAL connector packet. The UAL connector allows you to splice up to 3 wires in each connector. To use the connectors, follow these simple steps:

- 1. DO NOT STRIP INSULATION
- 2. Fold end of BZ-1 wires back 1/2" to double the wire thickness for splice.
- 3. Hold the connector button side down. Insert wires 24-18 AWG into the ports of the connector. Be sure the wires are inserted all the way into the end of the connector past the center of the button.
- 4. Crimp the button down using pliers until it is completely seated into the body of the connector.




When connecting to Winland products, follow the product instruction manual and use the following color code:

Red = Positive (
$$+$$
) **Black** = Negative ($-$)

VehicleAlert Connections - To install the BZ-1 Buzzer to the VehicleAlert Console first remove power from the console by unplugging the transformer. Using a wire cutter, cut the "**Red**" lead from the console connector (Not the "Sensor Probe" lead). Insert the two ends of the "**Console**" lead into two of the ports of the UAL connector. Then insert the "**Red**" lead from the "**Buzzer**" into the UAL connector. Make certain that the wires are inserted all the way into the end of the connector past the center of the button. Crimp the connector (use the crimping notes shown above).

Next connect the "Black" lead from the remote "Buzzer" to the "Black" lead from the "Console" using a UAL connector. Crimp the connector.

Using a wire cutter, cut the "**Black**" lead from the console connector (Not the "Sensor Probe" lead). Insert the two ends of the console lead into two ports of the UAL connector. Then insert the "**Grey**" lead from the console into the UAL connector. Crimp the connector.



CONNECT THE **BZ-1** TO **WINLAND PRODUCTS:**

ENVIROALERT.

EnviroAlert® EA200

Dual Zone Wireless Electronic Monitor:
Temperature, Humidity, Water Presence
EA200-12 (12VDC) and EA200-24 (24VDC)
Has one built-in ambient temperature probe
Connect up to 1 hard wired probe



EnviroAlert® EA400

Four Zone Wireless Electronic Monitor: Temperature, Humidity, Water Presence EA400-12 (12VDC) and EA400-24 (24VDC) Connect up to 4 hard wired probes



EnviroAlert® EA800

Eight Zone Wireless Electronic Monitor:

Temperature, Humidity, Water, Closed Contact, 4-20mA Connect up to 4 wireless and up to 4 hard wired probes Automatic data logging transferable via USB stick

Probe data
Event and alarm history



Eight Zone Wireless Electronic Monitor:

Temperature, Humidity, Water, Closed Contact, 4-20mA Connect up to 4 wireless and up to 4 hard wired probes Remote access via wired IP connection to

> Programming and real-time data viewing Probe data as well as alarm and event logs





WaterBug® WB-200 (12 or 24 VAC/DC) 6 Zone Unsupervised Water Probe:

- Includes 1 unsupervised surface probe (W-S-U)
- Accommodates up to 6 probes in parallel
- May purchase under carpet probe (W-UC-U)
- Will not alarm due to condensation or humidity
- Can be used to detect absence of water



ONE YEAR LIMITED WARRANTY

Winland Electronics, Inc. ("Winland") warrants to the end user/purchaser that each product of its manufacture shall be free from defects in material and factory workmanship for a period of one year from the date of purchase, when properly installed and operated under normal conditions according to Winland's instruction.

Winland's obligation under this warranty is limited to correcting, without charge, at its factory any part or parts thereof which shall be returned to the factory, by the original purchaser, transportation charges prepaid, within one year of the date of purchase and which upon examination, shall disclose to Winland's satisfaction to have been originally defective. Correction of such defects by repair to, or supplying replacements for, defective parts shall constitute fulfillment of all Winland's obligations to purchaser under this limited warranty. Repair service performed by Winland after one year from date of purchase will be for a reasonable service charge.

This limited warranty shall not apply to any of Winland's products which have been subject to misuse, negligence or accident or which have been repaired or altered outside of Winland's factory. The warranty is void if the Product's housing or cover is removed.

Winland shall not be liable for loss, damage or expense resulting, directly or indirectly, from the use of its products or any other cause.

This warranty shall be null and void in its entirety if: (i) the product is altered or modified in any way that is not consistent with the manufacturer's instructions, or (ii) the product is used with or connected to a device: (a) that such product is not intended to be used with or connected to, (b) is not otherwise consistent with the manufacturer's instructions, or (c) is not otherwise approved by the manufacturer.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSES, NON-INFRINGEMENT AND TITLE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, USAGE OF TRADE OR OTHERWISE. ALL OTHER REPRESENTATIONS MADE TO THE FUD USER/PURCHASER BY ANY OTHER PARTY ARE ALSO EXCLUDED. WINLAND SHALL NOT BE LIABLE TO ANY PERSON FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY DESCRIPTION, WHETHER ARISING OUT OF WARRANTY OR OTHER CONTRACT, NEGLIGENCE OR OTHER TORT, OR OTHERWISE. Under no circumstances shall Winland's liability under this limited warranty exceed the purchase price paid by the end user/purchaser for the product.

No person, agent or dealer is authorized to give warranties on behalf of Winland nor to assume for Winland any other liability in connection with any of its products.




WINLAND REMOTE BUZZER

Remote Annunciation for Winland products

CONTENTS

This package contains:

- 1 BZ-1 Remote Annunciator
- UAL Connectors
- 1 Installation/Operating Instructions Guide



BZ-1

SPECIFICATIONS

Power Requirement 11 to 26 VDC @ 10mA

Operating Temp 32° to 122°F (0° to 50°C); non-condensing environments

Indoor use only.

Buzzer 86 dB @ 30 cm @ 12 VDC. 3.5 kHz, continuous

Weight 0.65 lb (0.3 kg)

Dimensions 4.5 x 2.75 x 0.23" (11.43 x 6.99 x 0.58 cm)

Mounting Standard 1-gang switch mounting box

Warranty 1 Year Limited

Tech Support 8:00am - 5:00pm Central Time (800) 635-4269 • +1-507-625-7231 P www.winland.com



© 2012 Winland Electronics, Inc. Z1885 Rev E (08/2012)