INDUSTRIES

Our revolutionary software will allow you to initiate the fastest-possible response to any arising equipment issues, protect your inventory investment, maintain compliance with governmental regulations, avoid fines and costly lawsuits, and safeguard your reputation.

Healthcare



Winland **INSIGHT*** is an automated, cloud-based critical-condition monitoring service available within the healthcare industry.

It provides early detection of environmental threats to your perishable assets, ensuring that healthcare standards are continuously upheld.

Pharmaceutical



There is no compromising when it comes to pharmaceutical standards. Safety is of paramount importance-to your clients and to your reputation.

Protect your perishable assets with **INSIGHT** and position yourself as an industry leader in regulatory compliance.

Foodservice



Protect your perishable assets, and your reputation with Winland **INSIGHT**. Winland technology is essential to any comprehensive food-safety program.

Research Facilities



Winland technology is essential to your research facility, providing early detection of threats to your fragile assets, ensuring that standards are continuously upheld. **INSIGHT** is undaunted by the prospect of monitoring your delicate assets with its automated, cloud-based, critical-condition monitoring service.

Agriculture



With the majority of American farmland being industrial agriculture, and the growth of greenhouse facilities, Winland's **INSIGHT** is essential for your maximum yield.

Manufacturing



INSIGHT allows you to initiate the fastest-possible resolution to any arising equipment issues, protect you inventory investment, and maintain compliance with governmental regulations.

* Fee-based subscription required

Visit www.winland.com, call 800.635.4269 or email <u>techsupport@winland.com</u> to learn more.

WINLAND^M ELECTRONICS, INC.

Critical Environment Monitoring Specialists

Remove the obstacles, disruptions, distractions and concerns that impede a smoother running business. With the Winland Critical Environment Monitoring solution, you'll experience newfound freedom – and ability to focus on the very things that improve results and drive value.

The solution provides complete real-time visibility to temperature, water, gas, humidity and other physical irregularities in critical condition environments. Curb inventory and labor costs. Ensure compliance with storage regulations. Safeguard your business reputation and market position.





Critical Environmental Monitoring Solution INSIGHT

Newfound freedom comes complete with plenty of options – your options. You can design response plans, receive exception alerts, generate and distribute reports virtually any way you want them. You can monitor critical environment conditions two ways – on-line via any computer or smart device for real-time data access and/or integrate the solution with a trusted security system provider for 24×7 monitoring.



The Right Response

INSIGHT offers:

- The ability to log an acknowledgment, or reading of a condition.
- If needed, **INSIGHT** can present an action step to the respondent.
- The ability to develop customized and step-by-step response plans for any type of incident, type of product and more- with a few clicks of the system.
- Option for user to leave a comment which can be mandatory.
- The system will automatically generate an incident report that is distributed immediately after the response plan is completed.





Exception Alerts, Six Ways

When a sensor falls outside of its threshold, notifications can be sent to recipients in any of the ways users configure their notification preferences.

- Visual System Notification within the web-based application
- Email Alerts
- Text Messaging
- On-premises Audible and/or Visual Alarm
- Notification of Alert relayed to security provider monitoring station.
- Integrate notification of Alert into third-party or proprietary system.



Reporting and Analytics

Robust reporting capabilities with configurable and custom reports that can be accessed on-demand or distributed to individuals and groups at specified intervals with scheduled reporting.

Six of the most common system generated reports include:

- Sensor Detail Log Report
- Sensor Summary Log Report
- Sensor Acknowledgment Report
- Alert by Location Report
- Alert by Device Report
- Alert Response Summary



Ballant	Accest Adventuation Profes		Concess of		
Manage R	noorts.				
		-	-		
			_		
	TIMAT				
	Barboot Name Accest Adventured	un Pulles			~0
	Manage Reports				
				0 0	0
	Chosen to coule a new report or will an	minima manuf			Alexandre and a second s
					TROUGHOUSE COMPANY
	a manang			<u> </u>	
	The second se	assesses Aufes			
	CA	annatalar Pulles			
	Ca Excelored Backage Reports	ensiste Auto	/		~
	A Strange Reports	densenatos Pudios	_	• •	
-	Coses to costs a new report	energian and Antipa	1	• •	1000 1000 1000 1000 1000 1000 1000 100
	Cross to cost a two report	enerated Parks			
	Construction to construct a store to appendix	e nell ac colorgo oport	2		- 0-
	Closes to coale a new report Closes to coale a new report	r add as webby sport Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserved Reserve		O	
	Constraint of the second	r add as webling report		Annexe	
	Chan to survey and Chan to survey a survey of Chan to survey a survey of Consta to survey of Const	r eff ar exhibits sport File Sectory Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Constants Co	1000 800 800 800 800 800	Annue	
	Channel To France To	Annabel An Annabel Annabel Ann	Contel 9001 0 9001 0 9001 0 900 0 900000000	Annue A	
	Constant and a series of the second series of the second s	and a vibility spot and a vibility spot Second Seco	1000 2010 2010 2010 2010 2010 2010 2010	Annue A	
	Character Region (Control of Control of Cont	anneal an anna anna anna anna anna anna	Control 10 10 10 10 10 10 10 10 10 10 10 10 10	Annue	
	Choose be cards a serve grant of the control of the	and a soliding spot of all as soliding spot in all as solid in all as soliding spot in all as solid in all as soliding spot in all as solid in		Automatication	
		eeste Valge eeste Valge sport August eesting sport August eesting sport August eesting August eesting Au	- Casta - State - Stat	A server A serv	
•	Characterization of the second	Andread and a subling lagoont and an subling lagoont		Automatication of the second sec	

Safe and simple under the hood.





Its configurable enterprise structure simplifies remote management of devices in multiple locations or within different organizational groups.



Simplified Integration

Integrating alert relays into any wired or wireless security system is easy and enables 24×7 monitoring.

Standard APIs* (based on secure web services) facilitate data extraction from **INSIGHT** and integration with other applications.

* Available Upon Request



Robust System Security

The Winland solution protects stored and transmitted data's security, integrity and privacy.

It's a cloud-based platform with tiered infrastructure, application, encrypted proprietary communication protocol, and SSL data traffic.



Winland Healthcare Installation

This layout example shows many applications that could be monitored individually. The EA800-ip cons layout using one console with hardwired and wireless sensors. The console provides electronic data log

Key points:

- Connect up to 12 sensors via the EA800-ip (up to 8 wireless, up to 4 hardwired)
- The TEMP-L-S stainless steel sensor is used in most cooler/freezer applications
- The TEMP-L-W waterproof sensor can be immersed, i.e., heavily washed areas etc.
- The **TEMP-G-B** is our 6oz bottle of Glycerin with a grommet top
- Wireless sensor transmission range is 45' to 100' indoor (results may vary)
- Wireless sensors cannot be placed in coolers/ freezers (use a hardwired sensor connected to an external **EA-WMFS** sensor, see Zone 8 example)

Monitoring Zone





Hardwired Input Vaccine Refrigeration

Hardwired Inp **Blood**/Plasma

10

Additional wirele

available for futu

11



Console to Panel Connection

Auxilary

Alarm

Eight of the twelve available sensors can be connected via output relay to an alarm panel.

All EnviroAlert consoles have an auxiliary output relay to accommodate remote buzzers and strobes (or as an optional single output to the alarm panel).

Alarm Panel

Data Logging

INSIGHT* maintains device and sensor log data online for 18 months. Beyond 18 months and up to 36 months, log data can be obtained by emailing insightsupport@winland.com. *Requires a fee-based subscription.

• Locally, 10,000 data points per sensor are transferable to a USB memory stick.

0	ashboard Reports Accourt	t Administration Profi	les Wir	land Demo Sub	•			нер (
	Device Overview	•	All Devices	Alerts	Response	ling e Noom	el e Offline	= •
•	Alert						#2DE9	Sensor: Storeroom 103 (IN ALERT *
ó	Pharma 27 Des Moines, IA					0151 S Desi	14TH STREET Voines, IA 50320 1234567890	Response Plan: Pharma 1
9	Tue Jun 27 2017 14:02:32 G	dT-0500 (Central Daylight	Time)					1. Identify sensor location and condition causing abort.
	4 43 sec			De	vice Level Re	sponse Plan: Phi	ema 1	Add Notes (optional)
	Sensor Name/Location	Туре		Reading	Units	Low Lim	High Lim	
	Storeroom 103	Temp Blue						
	SUMP PUMP	Waterbug	199	Dry		NA	N/A	
	DOOR #3	NO Contact		Open		N/A	N/A	ACTION 1 COMPLETE
	STORAGE ROOM	Wireless Humidity	۲	39	%RH	1	79	
	COMPUTER ROOM	Wireless Temp		74	E	52	80	
	M OFFICE TEMP	Wireless Temp		74	P.	44	00	

ole was designed to monitor the entire gging reducing risk of employee error.





ZONE 3

Hardwired Input Medical Grade Vaccine Freezer

ZONE

Hardwired Input

TEMP-UL-S

Cooler/Freezer Monitoring

Coolers/freezers can be monitored using hardwire sensors or wireless sensors. Wireless monitoring requires the **EA-WMFS** with a sensor.

Hardwired Installation:

Select blue sensor TEMP-L-S or TEMP-L-W



ications which use an **EA-WMFS** wireless sensor ire the connection of a sensor for the specific ition to be monitored.

TEMP-L-S

TEMP-G-B



ss sensors re application



Pharmaceutical Drug Storage

Wireless Installation: Select EA-WTS or HAiii+

> **W-S-S** Supervised Water Sensor Supervised sensors will alarm if wire is severed as well as when water is detected

Wireless Input Freezer Door EA-WMFS + Door contact sensor

5

ZONE

ZONE 6 Wireless Input Laboratory

Wireless Installation: Select **EA-WHS or EA-WTS**



Wireless Input Water Presence Near Water Heater Wireless Installation: Select EA-WMFS + W-S-S

Hardware

EnviroAlert® EA800-ip

12 protection zones (4 wired and 8 wireless) with 9 form C relay outputs.



Specifications

Sensor Alarm Outputs	8 – Form C Relays (G
Auxiliary Alarm Output	1 – Form C Relay (<i>N</i>
Data Collection Frequency	30 seconds, 1, 5, 15
Power Requirements	11 to 26 VDC @ ≤50
Piezo Buzzer	88 dBA (min) @10 c
Operating Temperature Range	32° to 122°F (0° to 5
Console Dimensions	8.13 x 5.52 x 1.93" (2
Wireless Frequency	2.405 GHz – 2.480 C
Wireless Sensor Transmission Distance	45' to 100' indoor (<i>r</i>
Warranty	1 year

Form C Relays (Configurable) – Max 30 VDC @ 1 Amp resistive
Form C Relay (Non-Configurable) – Max 30 VDC @ 1 Amp resistive
0 seconds, 1, 5, 15, 30, 60, or 120 minutes (default 5 minutes)

I 1 to 26 VDC @ ≤500mA 38 dBA (min) @10 cm Continuous (*enable/disable for local audio alarm*) 32° to 122°F (0° to 50°C) Indoor Use Only 3.13 x 5.52 x 1.93" (20.6 x 14.0 x 4.9 cm) 2.405 GHz – 2.480 GHz, 16 channels 45' to 100' indoor (*results may vary*) 1 year

Wireless Sensors

Power Requirements: Battery Power: 2 – AA Alkaline Batteries or Line Power: +12VDC @ <100 mA

Wireless Temperature Range SensorEA-WTSWireless Humidity SensorEA-WHSWireless MultifunctionEA-WMFS

+32 to +122° F (0 to +50° C) 5% to 95% Relative Humidity

Utilize any of the standard hardwired sensors (*excluding the HAIII*+) in conjunction with the Wireless Sensor Adapter.

Wired Sensors and Accessories

Ultra Low Temperature Thermistor – Stainless Steel	TEMP-UL-S	-148 to +32° F (-100 to 0° C) or -112 to +32° F (-80 to 0° C) (with EA-WMFS Wireless)
High Temperature Thermistor – Stainless Steel	TEMP-H-S	+32 to +302° F (0 to +150° C)
Low Temperature Thermistor – Stainless Steel	TEMP-L-S	-58 to +158° F (-50 to +70° C)
Low Temperature Thermistor – Waterproof	TEMP-L-W	-58 to +158° F (-50 to +70° C)
High Temperature Thermistor – Waterproof	TEMP-H-W	+32 to +221° F (0 to +105° C)
WaterBug [®] – Supervised Surface Sensor	W-S-S	Water Presence Detection
WaterBug [®] – Supervised Under Carpet Sensor	W-UC-S	Water Presence Detection (for use under carpet)
Humid-Alert [®] - Humidity Sensor	HA-III+	Humidity Sensing Range: 5-95% RH +- 5% @ 77° F
6 oz Bottle of Glycerin and Grommet Cap	TEMP-G-B	
Temp Probe Flat Cable Splice Kit – 5'(1.53 m)	TEMP-S-K	

Monitor other critical environments with 4-20mA Sensors (Gas, Light, Extreme Temps, pH, Pressure, etc.)





For additional assistance contact tech support at 800.635.4269 Ext. 1 or email techsupport@winland.com



Critical Condition Monitoring Application Data

Step 1 - Evaluate Job Sites for Critical Co	ndition Monitoring	1							
Applications									
Pharmaceutical Drug Storage Foo	d Services/Storage	Computer Room	Heat/Vibration Monitoring						
Blood/Plasma Storage Deli	Coolers	Hot Water Heaters	Livestock Facility						
Clean Rooms Wall	k-in Freezers	HVAC Monitoring	Warehouse						
Other:Othe	r:	Other:							
tep 2 - Determine Customer Requireme	ents		Y N						
· · · · · · · · · · · · · · · · · · ·	- NI-	Emails, Texts and Reporting	_Yes No						
Integrate with Existing Alarm System:Ye	s <u> </u>	Data Logging Required:	_YesNo						
Local Alarm Required:Ye	s <u>No</u>	NIST Calibration Required:	_YesNo						
Coolers:		Freezers:							
Reach InEnclosed CaseWalk	-in	Reach InEnclosed Ca	aseWalk-in						
Other:		Other:							
Cooler Count: Fan Cour	nt:	Freezer Count:	Fan Count:						
Cooler Temp Range:		_ Freezer Temp Range:							
Cooler Contents:		Freezer Contents:							
Defrost Cycle Length:		Defrost Cycle Length:							
Humidity:		Toxic Gases:							
Number of Locations:		Gas Type:							
High Setting: Low Setting	າg:	Unit of Measure:							
Water Sensing:		Other:							
Number of Locations:									

Step 3 – Select Product Quantity

 EA200	Console (on-board temp/1 hardwire sensor input)
 _ EA400	Console (4 hardwire sensor inputs)
 EA800-ip	Console (up to 4 wired sensors, up to 8 wireless sensors)
 TEMP-L-S	Low Temperature Sensor, Stainless Steel
 _ TEMP-L-W	Low Temperature Sensor, Waterproof
 TEMP-H-S	High Temperature Sensor, Stainless Steel
 TEMP-H-W	High Temperature Sensor, Waterproof
 TEMP-UL-S	Ultra Low Temperature Sensor, Stainless Steel
 - TEMP-G-B	6 oz Bottle of Glycerin and Grommet Cap
 EA-WTS	Temperature Sensor, Wireless
 EA-WHS	Humidity Sensor, Wireless
 EA-WMFS	Multi-Function Sensor, Wireless
 - HA-III+	Humid-Alert [®] Electronic Humidity Sensor
 - W-S-S	WaterBug [®] Water Sensor, Supervised
 - W-UC-S	WaterBug® Under Carpet Water Sensor, Supervised
 12VDCT	12-Volt Power Transformer
 - Sensors wit	h 4-20 mA Connection

Step 4 – Sensor Placement

Create diagram of sensor locations